

Screen Size 4:3		Throw distance	
Diagonal*	Width*	Min*	Max*
40	32	47	57
60	48	71	86
80	64	95	115
100	80	119	143
120	96	143	172
150	120	179	216
200	160	239	288

Throw ratio: 1.5-1.8:1 (distance:width)
* Measured in inches



- 1,600 ANSI Lumens
- 5.1 lbs.
- Vertical Keystone Correction
- RGB / Composite / S-video Inputs
- Component Video Shared with VGA
- Native XGA Resolution
- Contrast Ratio 500:1
- Auto Configuration (H-Size, Position)
- Approx. 3,000 Hour Lamp Life Whisper Mode
- Reverse Image Function for Ceiling Mount
- Gamma Correction
- Freeze Function
- Magnify (4x)
- 33dB (Whisper Mode)
- 2-3 Pull Down
- Throw Ratio 1.5-1.8:1
- Optical Zoom & Digital Zoom x 1.2

SPECIFICATIONS

Model Number	CP-RX61		
Liquid crystal panel structure	0.6" polysilicon active-matrix TFT x 3 with micro lens		
Resolution	Video	540 TV Lines	
	RGB	1024 Dots x 768 Lines	
Colors	16.7 million colors		
Aspect ratio	Native 4:3; or 16:9 Compatible		
Lens	F1.6-1.9, Manual Zoom x 1.2, manual focus		
Throw ratio (distance:width)	1.5~1.8:1		
Lamp	165W UHB		
Brightness	1,600 ANSI Lumens		
Contrast Ratio	500:1		
Expected lamp life	Approx. 2,000 hours (Approx. 3,000 hours in Whisper Mode)		
Speakers	1W x1		
Power supply	AC100-120V/AC220-240V, 50/60 Hz, Auto Switching		
Power consumption	240W		
Approvals	UL60950/C-UL, FCC Class B, CE, EN60950		
Operating temperature	0 ~ 35°C (32° ~ 95°F)		
Inputs	RGB	VGA, SVGA, XGA, SXGA, UXGA MAC 16", 480i, 576i, 480p, 720p, 1080i	
	Composite Video Plug & Play	NTSC, NTSC4.43, PAL (-BGDh), SECAM, PAL-M, PAL-N DDC1/2B	
Acoustic noise level	38dB (33dB in Whisper Mode)		
Vertical keystone correction	Digital Keystone +/- 15°		
Input/Output terminals	Data input	RGB	15-pin D-sub connector x 2
	Video input	S-video	Mini DIN 4-pin connector x 1
		Composite video	RCA jack x 1
		Component video	Shared with VGA 1 15-pin D-sub
	Audio input	Stereo mini jack x1	
Audio output	Stereo mini jack x1		
Control terminals	9-pin D-sub connector x 1 RS-232C (Serial)		
Chassis	Dimensions	11.92" x 2.87" x 7.94" (W x H x D)	
	Weight	5.1 lbs.	
	Supplied accessories	Remote control, batteries (AA), power cord, RGB cable, Filter Cover for Ceiling Mount Use, Safety Instruction Guide, User Manual (CD)	
Replacement parts	Lamp	CPRS55LAMP	
	Remote control	HL02212	
	Filter	NJ20922	