

HITACHI

Inspire the Next

CP-X995W



- 4,500 ANSI Lumens
- Native XGA Resolution
- 14 lbs.
- 16:9 Mode
- Contrast Ratio 300:1
- 2 RGB Inputs/RGB Output
- Composite/Component/S-Video/DVI Input
- Motion Adaptive Progressive Scan
- Vertical & Horizontal Keystone Correction
- My Screen (user programmable start-up screen and blank screen)
- HDTV Theater Ready
- 40/36dB (Whisper mode)
- Switchable IR Receiver
- Noise Reduction System
- Black Enhancement System
- Picture-in-Picture
- FCC Class B
- Digital zoom (x 4)
- Picture freeze function
- Cinema Mode (3/2 Pull-Down System)

SPECIFICATIONS

Model name		CP-X995W	
Liquid crystal panel structure		1.3" polysilicon active-matrix TFT x 3	
Number of pixels		786, 432 pixels (H 1,024 x V 768)	
Resolution		1,024 x 768 color pixels	
Colors		16.7 million colors	
Aspect ratio		Native 4:3 (16:9 resizing mode)	
Lens		Power zoom (F=1.7 - 2.3) 1:1.3, Power focus	
Throw ratio (distance:width)		1.72 ~ 2.41 : 1	
Lamp		275W UHB	
Brightness		4,500 ANSI lumens (Approx 3,600 lumens in whisper mode)	
Expected lamp life		2,000 hours	
Contrast ratio		300 : 1	
Speakers		1.2W + 1.2W (Stereo)	
Power supply		AC100-120V/AC220-240V	
Power consumption		440W	
Operating temperature		32°F ~ 95°F (0° ~ 35°C)	
Input signals		RGB Composite video Component video	
		VGA, SVGA, XGA, SXGA (COMPRESSED), MAC13", MAC16" NTSC, NTSC4.43, PAL, PAL60, PAL-N, PAL-M, SECAM 480i, 575i, 480p, 1,080i, 720p	
Acoustic noise level		40dB (36dB in whisper mode)	
H sync		15kHz ~ 80kHz	
V sync		50Hz ~ 120Hz	
Vertical keystone correction		Digital keystone +/- 15°	
Horizontal keystone correction		Digital keystone +/- 5°	
Approvals		UL, C-UL, FCC Class B, CE, TUV	
Input/Output terminals	RGB input	Digital RGB	DVI-D connector x 1
		Analog RGB	15-pin D-sub connector x 2
		Audio	Stereo mini jack x 2
	RGB output	RGB	15-pin D-sub connector x 1
		Audio	Stereo mini jack x 1
	Video input	S-video	Mini-DIN 4 pin connector x 1
Composite video		RCA jack x 1	
Component video		RCA jack x 3	
Audio		RCA jack x 2 (L/R)	
Control terminals		15-pin D-sub connector x 1	
		USB connector (USB mouse) x 1	
Compatible controls		PS/2, ADB serial, RS-232C (serial)	
Dimensions		11.4" x 5.5" x 13.6" (W x H x D)	
Chassis	Weight	14.3 lbs.	
	Supplied accessories	Remote control with laser pointer, Power cord, RGB cable, RCA component cable, batteries (AA), PS/2 mouse cable, operator/safety manual	
Spare/option accessories	Lamp	CPX990 LAMP (Part #: DT00491)	
	Remote control	(Part #: HL01811)	
	Wide angle lens	(Part #: WL-201)	



Screen Size 4.3		Throw distance	
Diagonal*	Width*	Min*	Max*
40	32	55	73
60	48	85	114
80	64	114	151
100	80	144	191
120	96	176	231
150	120	220	282
200	160	291	386

Throw ratio: 1.72-2.41:1 (distance:width)

*: Measured in inches

CP-X990/CP-X995 Dimensions

(incl.protruding part)

