


ED-A100 Features & Benefits

HITACHI
Inspire the Next

 My Image / Campus Notification System

 Closed Captioning



Key Features

2000 ANSI lumen	Bright and clear images in any medium size venue.
Ultra Short Throw lens	The Hitachi ED-A100 features Ultra Short Throw lens which will project a 60" image at 1.4 feet. This not only prevents obstructions but also means no shadows and no light shinning in the presenter's eyes.
Lamp life approximately 3,000 Hours (Whisper Mode)*	Another key to low total cost of ownership is a long life lamp. The Ed-A100 lamp is rated at 2000 hours in standard mode and 3000 hours in whisper mode
7 watt Audio Output	7W audio output eliminates the need to connect external speakers.
Network Control, Maintenance and Security	Projector Management Application (PJMan) allows users to monitor, and control multiple projectors over LAN. Features include scheduling of events, e-mail alerts for reactive and routine maintenance. Hitachi's Projector Control Application ('PJCtrl') allows a user to control the functions of their Hitachi 3LCD Projector via a 'Toolbar' on their PC. Since all of the functions for controlling the projector are on the PC, PJCtrl can help to reduce costs associated with lost remote controls, battery replacement.
My Image (E-shot)	Making it possible for AV/IT Administrators take control of the projector and instantly display stored images across an entire campus
Power Saving Mode	The Saving mode reduces the stand-by power consumption to 5W with limitation of some features.
Lamp door on Top	Easy maintenance is another attractive function of the ED-A100, as its lamp door is on top of the mode
Transition Detector	A security sensor located inside the projector recognizes when the projector has been moved. Moving the projector with out using the correct PIN Code will disable the projector. Exclusive to Hitachi
Template Function	Line templates in the projector menu can help when writing on a whiteboard. There are four types of line templates to choose from. Exclusive to Hitachi
White Board Mode	Limits the peak white by changing the gamma curve limiting its brightness when used with a whiteboard to protect the eye health of teachers and students. Exclusive to Hitachi
Input source naming	Users can name input sources in simple language instead of factory default name. Exclusive to Hitachi
IR remote Frequency Change	To avoid conflict with fluorescent lights or IrDA (IR signal) from notebook PC, the frequency of the IR remote control can be changed from the menu. Exclusive to Hitachi
My Button My source-Doc camera	There are 2 customizable buttons on the remote control that users can program to execute any projector command such as: Direct input (RGB1, S-video etc.), Picture Mode, Filter Reset. My source adds a third source button labeled document camera for quick access to another important teaching tool.
PIN Lock / My Text My Screen PIN Lock	PIN lock protection can limit projector users. My Screen PIN Lock keeps captured images on the startup screen. Users can set a school's name or company's logo to "My Screen" clearly identifying ownership My Text provides the ability to write text on the start up screen. Example, model name, serial number, or location.
Serial Number Label on Side	It is convenient for users or auditors to be able to check the model name and serial number of an asset easily when the product is ceiling mounted. The label is upside-down and easily viewable for ceiling-use. Exclusive to Hitachi
Closed Captioning	CC1, CC2, CC3, CC4

* Actual lamp life will vary by individual lamp and based on environmental conditions, selected operating mode, user settings and usage. Hours of average lamp life specified are not guaranteed and do not constitute part of the product or lamp warranty. Lamp brightness decreases over time.