

XL4U

COLORVIEW™ PROJECTOR



EXTREME XGA VALUE
WITH SECURITY

THREE-LEVEL PASSWORD PROTECTION

 **MITSUBISHI
ELECTRIC**
PRESENTATION PRODUCTS
REVOLUTIONIZINGCOLOR™

ColorView
NATURAL COLOR MATRIX™

sRGB

1500 ANSI LUMENS

VERTICAL DIGITAL
KEYSTONE ADJUSTMENT

450:1 CONTRAST RATIO

XGA 1024 X 768

600 VIEWABLE VIDEO
LINES

HDTV-READY

SHORT-THROW LENS

The XL4U ColorView projector is one of Mitsubishi's lightest weight ultraportables, and offers exceptional XGA performance, reliability, and overall value. Plus, a versatile array of remote control "password-activated" security features helps to control projector usage and further protect your investment.

- Exclusive, award-winning ColorView Natural Color Matrix for rich, vivid colors
- sRGB color profile technology ensures standard uniform color reproduction regardless of the type of display used
- Remote control password-activated security features include: Block complete usage of the projector; permit usage of the projector, but not change the menu; or block changing of the splash screen
- 1500 ANSI lumens for bright presentations
- 450:1 contrast ratio for exceptional color depth and clarity
- User selectable gamma correction
- Three-year parts and labor warranty and 90-day warranty on the lamp (both warranties available in U.S. and Canada), toll-free technical support, plus three-year Express Replacement Assistance (ERA) program that guarantees free replacement product shipped overnight for next business day delivery when and where available

Designed for

Microsoft
Windows NT
Windows 98


Mac



ISO
9001
QUALITY
ASSURANCE


3
YEAR
WARRANTY


E.R.A.
EXPRESS
REPLACEMENT
ASSISTANCE
3 YEAR WARRANTY

XL4U

COLORVIEW™ PROJECTOR



SPECIFICATIONS

COLORVIEW™ NATURAL COLOR MATRIX

The XL4U produces vivid colors that precisely match their real-life counterparts, as well as giving you the ability to precisely adjust color saturation and control color tones.



Without ColorView With ColorView

PRECISE COLOR REPRODUCTION WITH sRGB



Developed to ensure standard, uniform color reproduction regardless of the type of display used, sRGB color profile uses color coordinates common to all display technologies.




VERTICAL DIGITAL KEYSTONE CORRECTION

Absolutely essential for portable projectors, Digital Keystone Correction reduces image distortion by allowing for vertical correction to create a more natural-looking picture even when it is difficult to set up the unit perfectly perpendicular with the screen. This important feature allows you to project at an angle without worrying about trapezoid image distortion or zigzagging.



Vertical distortion No distortion

INPUT AND OUTPUT TERMINALS




1. USB
2. RS-232C Terminal
3. Computer Out Terminal
4. Computer In Terminal
5. Video Input Terminal
6. S-Video Input Terminal
7. Audio Input Terminal
8. Ground Terminal
9. Power Jack

SPECIFICATIONS

Display Technology	0.7" Polysilicon LCD panel x3
Native Resolution	XGA 1024 x 768, 600 video lines
Max. Resolution (compressed)	SXGA 1280 x 1024
Brightness	1500 ANSI Lumens
Contrast Ratio	450:1 (full-on, full-off)
Lens Throw Ratio	1.56 ~ 1.87
Projection Lens	F = 2.0 ~ 2.3, f = 23 - 27 mm
Zoom/Focus Adjustment	Manual zoom and manual focus lens (zoom ratio 1.2:1)
Picture Size (4:3 aspect ratio)	40" ~ 300" (100" = 3.8 m)
User Replaceable Lamp*	180 W NSH lamp; 3000 hour lamp life (low mode)
Computer Compatibility	VGA ~ SXGA 640 x 480 ~ 1024 x 768, compressed 1280 x 1024, Sync on green available
Video Compatibility	NTSC/NTSC 4.43/PAL (including PAL-M, NJ)/SECAM/PAL-60/DVD (component) 480P (525i, 525P) HDTV-ready (1080i, 720P)
Input Terminals	RGB: mini D-sub 15 pin x 1; Video: RCA x 1 = S video x 1; PC/video audio; Stereo RCA x 1
Output Terminals	RGB: mini D-sub 15 x 1
Communication Terminals	RS-232C x 1 (direct command is available, DIN 8 pin) USB terminal for page up/down
Audio Speaker	Mono 2W
Scanning Frequency	Horizontal: 15 - 100 kHz, Vertical: 50 - 120 Hz, Dot clock: max. 140 MHz
Remote Control	Wireless, card-type remote. Full projector and computer control with USB mouse cursor control. Powerpoint page up/down via USB
Power Consumption	230 W
Dimensions (W x H x D)	10.8 x 2.7 x 10.2" (274 x 69 x 260 mm) (Excluding stand)
Weight	5.9 lbs (2.7 kg)
Power Supply	AC 100 ~ 240V / ±10%, 50/60 Hz
Safety Approvals	CSA, CSA NRT L/C, FCC Class-B
Warranty	Three-year parts and labor warranty and 90 day warranty on lamp (both warranties available in U.S. and Canada). Also includes three-year Express Replacement Assistance program that guarantees free replacement projector shipped overnight for next business day delivery when and where available
Accessories	Standard: AC power cable; video cable; RS-232C cable; AV cable; USB cable; remote unit; soft carrying case; lens cap; user manual CD; quick reference card Optional: Spare lamp (VLT-XL8LP); remote unit (learning, laser, mouse) (Part No. R-SC11); ceiling mount bracket (Part No. XL8CM); wheeled soft carrying case with computer (Part No. XL1SSCC); wheeled ATA-approved carrying case (Part No. XL1-ATAC)
Special Features	ColorView Natural Color Matrix; sRGB color compliance; line doubler; vertical and horizontal keystone correction (vertical automatic); user selectable gamma correction; user programmable splash screen; 3D color uniformity; 3D Y/C digital comb filter and 3D noise reduction; 10 language OSD; digital expand zoom with single window; short-throw lens

For more information on the XL4U or any of Mitsubishi's other projectors or presentation products, contact Mitsubishi Digital Electronics today. Detailed technical specifications available upon request.



Screen Size			Distance from screen (L)/(approximate)		Height Projected (inch) (H)
Diagonal (inch)	Width (inch)	Height (inch)	Maximum Zoom (WIDE) (inch)	Minimum Zoom (TELE) (inch)	
40	32	24	49	60	2.4
60	48	36	75	91	3.6
80	64	48	101	121	4.9
100	80	60	126	152	6.0
150	120	90	194	229	9.0
200	160	120	255	306	12.0
250	200	150	319	383	15.0
300	240	180	383	-	18.0

The above numbers are approximate, and may be slightly different from the actual measurements.

To find the approximate distance between the projector and screen:
Multiply the width of the screen x 1.56 (max.); multiply the width of the screen x 1.87 (min.).
Refer to the chart for recommended distances in maximum zoom and minimum zoom.

©2003 Mitsubishi Digital Electronics America, Inc. Standard features, options and specifications subject to change without notice. Microsoft, Windows, and the Windows logo are registered trademarks of Microsoft Corporation. Mac and the Mac logo are trademarks of Apple Computer, Inc., registered in the U.S. and other countries. All other trademarks or registered trademarks are the property of their respective holders. *The projector lamp contains mercury. Please dispose of properly.

Printed on 50% recycled paper including 20% post-consumer fibers.

Mitsubishi Digital Electronics America, Inc.
Presentation Products Division
9351 Jeronimo Road
Irvine, CA 92618
Toll Free: 888-307-0349
email: ppinfo@mea.com

Technical Support:
Toll Free: 888-307-0309
Email: tsupport@mdea.me.com

Canada:
Mitsubishi Electric Sales Canada Inc.
Information Technologies Group
Markham, Ontario
905-475-7728
www.mitsubishielectric.ca

www.mitsubishi-presentations.com