

Specifications	U5-232	U5-132
Projection System	DLP™	
Panel	DMD XGA x 1	
Resolution	1024 pixels x 768 pixels	
Brightness	Normal mode: 2000 lm Bright mode: 3000 lm (Eco-mode: approximately 20% less brightness)	Normal mode: 2000 lm (Eco-mode: approximately 20% less brightness)
Contrast Ratio	2000:1 (Full on/off)	
Aspect Ratio	4:3, supports 16:9	
Projection Lens	F2.6-2.9, f= 18.4-22.1 mm 1:1.2 Manual Zoom, Manual Focus	
Light Resource	200-watt High Performance Compact Lamp	
Color Palette	16.7 million colors	
Projecting Position	Front/Rear, Table/Ceiling	
Projection Distance	1.2-8.0 m	
Image Size	38"-300" diagonal	
RGB Signal (Input)	SXGA (Compression), XGA (True), SVGA/VGA (Expansion/True)	
Video Signal	NTSC3.58, NTSC4.43, PAL, PAL_N, PAL_M, PAL60, SECAM, YCbCr (NTSC, PAL), YPbPr (480p, 576p, 1080i, 720p)	
Horizontal Synch Range	15-80 kHz	
Vertical Synch Range	50-85 Hz	
Audio	Mono 0.8-watt	
Terminals(Input)	RGB/YCbCr/YPbPr: Mini D-Sub 15 pin x 1 Composite Video: RCA x 1 S-Video: Mini DIN 4 pin x 1 Audio (RGB/Video): ø3.5 mm Stereo Mini Jack x 1 PC Control: D-Sub 9 pin x 1 Remote Mouse: USB Type B x 1	
Color	Silver	
Dimensions Excluding Lens and Stand	60 mm (H) x 216 mm (W) x 252 mm (L)	
Weight	2.0 kg	

Power Supply	100-240 V AC at 50/60 Hz	
Power Consumption	280 watts (Normal mode), 250 watts (Eco-mode)	
Environment	32-95 °F/5-35 °C	
On-Screen Display Languages	English/German/French/Italian/Spanish/Swedish/Korean/Chinese/Japanese	
Functions	Full-Auto Adjustment Digital Keystone Correction (20 degrees) Digital Zoom (2x) Freeze Mute Color B/W Switching Quick Color Adjustment Presentation Timer Security Password	Full-Auto Adjustment Digital Keystone Correction (20 degrees) Digital Zoom (2x) Freeze Mute Quick Color Adjustment Presentation Timer Security Password
Accessories	Lens Cap x 1 IR Remote Control x 1 AAA Batteries (for Remote Control) x 2 Power Cable (1.8 m) x 1 VGA Cable (Mini D-sub 15 pin/2 m) x 1 S-Video Cable (Mini DIN 4 pin/2 m) x 1 Video Cable (RCA/2 m) x 1 Audio Cable (ø3.5 mm Mini Plug/2 m) x 1 Mini Jack to RCA Adapter (ø3.5 mm Stereo Mini Jack - RCA/0.15 m) x 1 USB Cable (Mini-B - Type A/2 m) x 1 Soft Case x 1 User's Manual (CD-ROM) x 1 User's Manual (Simplified Edition) x 1	
Optional Accessories	Ceiling Mount Kit User-Replaceable Lamp Unit	